

PIN RECEPTACLES

FOR 1,02 - 1,27 DIAMETER PINS (#02 CONTACT)
FOR 1,02 - 1,52 DIAMETER PINS (#03 CONTACT)

<p>0355 0355-0-15-XX-02-XX-10-0 Solder mount in 2,59 min. mounting hole</p>	<p>0354 0354-0-15-XX-02-XX-10-0 Pentagonal press-fit in 2,64 min. plated through-hole</p>	<p>3490 3490-0-15-XX-02-XX-10-0 Press-fit in 2,31 mounting hole</p>	<p>3808 3808-0-15-XX-02-XX-10-0 Press-fit in 2,29 mounting hole</p>
<p>9184 9184-0-15-XX-02-XX-40-0 Bottom entry, surface mount 2,34 min. plated through-hole Also available on carrier tape, See page 194.12 for Tape & Reel details</p>	<p>9222 9222-2-15-XX-02-XX-40-0 Bottom entry, surface mount 2,08 min. plated through-hole Also available on carrier tape, See page 194.12 for Tape & Reel details</p>	<p>4064 4064-0-18-XX-03-XX-40-0 Surface mount Also available on 16mm wide carrier tape: 2,400 parts per 330mm reel See page 194.13 for Tape & Reel details</p>	

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard
Contact Material: Beryllium Copper Alloy 172, HT
Dimensions: Millimeters
Tolerances On: Lengths: ± 0,13
 Diameters: ± 0,051
 Angles: ± 2°



ORDER CODE: XXXX - X - XX - XX - 02 - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#02 or #03 CONTACT (DATA ON PAGE 259)
 (For alternate contact choices, see group F on page 248)

