

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

| LOC | DIST | REVISIONS | | | | | |
|-----|------|-----------|---------|---------------|---------|-----|------|
| J | - | P | LTR | DESCRIPTION | DATE | DWN | APVD |
| | | E3 | REVISED | ECR-08-025567 | 100CT08 | TS | KB |

プリント基板取付寸法図
(MOUNTING DIMENSIONS FOR P. C. BOARD)

注
(NOTES) 1. 板厚: 1.6 ±0.15
(P. C. B. THICKNESS, 1.6 ±0.15)
2. 公差: ±0.1
(TOLERANCE, ±0.1)

1. 嵌合相手ハウジング; 172317
2. [A]面より2mmの範囲で測定のこと
3. 全面ニッケルメッキ上に接触部分は金めっき
ハンダ付け部は、ハンダメッキ
4. 推奨取付けねじ; JIS B 1115 又は、1122 タッピングねじに
なべ1種又は2種、呼び径3で締付けた後、ハンダ付けをする
5. 金及び、錫めっき混合タイプの金めっき配置図
下図参照のこと
6. 適用製品規格 No.108-5157

- 1 THE MATING PLUG HSG PART NUMBER ; 172317
- 2 TO BE MEASURED WITHIN 2mm FROM [A]
- 3 GOLD PLATING FOR CONTACT AREA AND TIN-LEAD
PLATING FOR SOLDERING AREA OVER ALL-OVER
NICKEL PLATING.
- 4 RECOMMENDED MOUNTING SCREW; 3mmDIA, PAN HEAD,
CLASS 1&2 TAPPING SCREW SPECIFIED IN JIS
B1115, B1122
- 5 LAYOUT OF GOLD PLATING CONTACTS ; [] MARK
(MIXED GOLD PLATING AND PRE-TINNED CONTACTS)

< VIEW FROM "B" DIRECTION >

6 APPLICABLE PRODUCT. SPEC NO. 108-5157

| | | | | | |
|----------|-------|---------------------------------------|----------------------|---------------------------|-------------------|
| | [A] | SELECTIVE TIN (MATTE) | SELECTIVE GOLD | 白色 WHITE | 2-5172730-1 |
| OBSOLETE | — / — | TIN-LEAD | | 白色 WHITE | 4-172730-1 |
| | [A] | TIN-LEAD | SELECTIVE GOLD [A] | 白色 WHITE | 2-172730-1 |
| OBSOLETE | — / — | PRE-TIN | | 黄色 YELLOW | 1-172730-7 |
| OBSOLETE | — / — | TIN-LEAD | SELECTIVE GOLD [A] | 灰色 GRAY | 1-172730-6 |
| OBSOLETE | — / — | TIN-LEAD | SELECTIVE GOLD [A] | 白色 WHITE | 1-172730-1 |
| | — / — | PRE-TIN | | 白色 WHITE | 172730-1 |
| | [A] | 半田付け部 SOLDERING SIDE | 嵌合部側 CONTACT SIDE | ハウジング色 HOUSING COLOR | 型番 PART NUMBER |
| | [A] | 金めっき配置図 LAYOUT OF GOLD PL. CONTACT | | コンタクト仕上 CONTACT FINISH | |

THIS DRAWING IS A CONTROLLED DOCUMENT.

| | | | | |
|----------------------------|---|--|---|--|
| DIMENSIONS: 単位: 概 mm | TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差 | DWN T.SHINOHARA 09MAY07 | Tyco Electronics Corporation Kawasaki, Japan | |
| | 0 PLC ± - | CHK K.BETSUI 09MAY07 | PULSE LOCK CONNECTOR 24POSITION CAP HOUSING ASSEMBLY | |
| | 1 PLC ± - | APVD K.BETSUI 09MAY07 | | |
| | 2 PLC ± - | PRODUCT SPEC 製品規格 | NAME 名称 | SIZE CAGE CODE DRAWING NO A3 00779 C-172730 |
| | 3 PLC ± - | APPLICATION SPEC 取付適用規格 | RESTRICTED TO | |
| | 4 PLC ± - | WEIGHT - | SCALE 尺度 1:1 | SHEET 1 OF 1 REV E3 |
| | ANGLES ± - | MATERIAL 材料 HSG: PBT CONTACT: BRASS | CUSTOMER DRAWING | |

AMP 1470-19 REV 31MAR2000