


# M12 Panel feed-through HARAX® A-coded



Mating face




A-coding  
Mating face  
acc. to IEC 61076-2-101



## Applications / Advantages

03

- Actor and sensor applications
- For panel feed-through or PCB, straight version in IP20 or IP67, with or without assembled pigtail
- Available with crimp resp. HARAX® rapid termination
- Quick and easy assembly

| Identification  | Part No.              | Drawing   | Dimensions in mm |
|---|-----------------------|---|------------------|
| <p><b>HARAX® Panel feed-through</b></p>  <p>Male<br/>4 poles, A-coding<br/>0.14 - 0.34 mm<sup>2</sup> / AWG 26 - 22</p> <p>Panel thickness<br/>min. 2.5 mm<br/>max. 4.5 mm</p> | <p>21 03 321 1425</p> | <p>Gesamtlänge im verschraubten Zustand ca. 51,5mm<br/>complete length when assembled app. 51,5mm</p> <p>18,4</p> <p>M12x1<br/>M16x1,5<br/>M16x1</p> <p>SW17<br/>width across flats 17</p> <p>SW13<br/>width across flats 13</p> <p>Kabel/cable <math>\phi</math>4,5-5,4mm<br/>(transparent/transparent)</p> <p>Kabel/cable <math>\phi</math>5,5-7,2mm<br/>(schwarz/black)</p> <p>Kabel/cable <math>\phi</math>7-8,8mm<br/>(beige/beige)</p> <p><math>\phi</math>16,3 <math>\pm</math>0,2</p> <p>15,4 <math>\pm</math>0,2</p> <p>SW20</p> |                  |

03  
26