

Specification Sheet

Part Number: TAG15T3-795



Thermal Transfer Labels, 1.0" x .5", 3 Across, Polyester, Silver, 10,000/roll

Article Number	596-15795
Type	TAG15T3
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">•Metalized polyester has a matte finish, allowing for the highest resolution and print contrast.•The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.
Quantity Per	roll

Product Description

HellermannTyton's metalized polyester labels include a layer of metallic particles that give the appearance of being made of metal. Applications include asset tracking and product rating plates. The high operating temperature makes them suitable for use on electronic equipment. Great for replacing expensive metal stampings, engravings and even silk screened rating plates, the printed labels offer high quality imaging for text and graphics and can be permanently placed on a wide variety of flat surfaces.

Short Description	Thermal Transfer Labels, 1.0" x .5", 3 Across, Polyester, Silver, 10,000/roll
Global Part Name	TAG15T3-795-WH
Width W (Imperial)	1.0
Width W (Metric)	25.4
Thickness T (Metric)	64.0
Height H (Imperial)	0.5
Height H (Metric)	12.7
Width of Liner (Metric)	85.09
Width of Liner (imperial)	3.35
Material	Type 795, Polyester (PET)
Material Shortcut	795
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +300°F (-40°C to +149°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL-Recognized
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	10000
Package Quantity (Metric)	10000
Customs Number	3919102055
Labels per Column	1
Labels per Row	3
Weight (Metric)	0.521
Weight (Imperial)	1.14