



1. THIS RCPT. IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
 2. MAX WIRE INSUL TO BE USED WITH THIS RCPT IS .054 DIA
 3. METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
 4. PACKAGE MARKED M 24308/2-301F
 5. THIS RCPT. WILL ACCEPT SIZE 22 SOCKET CONTACT M 24308/12 OR AMP # 204351
- AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
 UL/CSA DESIGNATION MARKED IN THIS AREA, OPTIONAL

OBSOLETE	PHENOLIC COLOR: BLACK	204532-2
	DIALYL PATHALATE COLOR: BLUE	204532-1
	INSERT MAT'L	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN: C.C. THOMAS 12-4-87	OK: F.C. BALLEW 1-25-88	APVD: F.C. BALLEW 1-25-88	NAME: F.C. BALLEW	PRODUCT SPEC: ---	APPLICATION SPEC: ---	SIZE: ---	CAGE CODE: ---	DRAWING NO: ---	RESTRICTED TO: ---
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± .005	4 PLC ± -	ANGLES ± 0'30"	FINISH: SEE CALLOUTS	WEIGHT: ---	SCALE: 4:1	SHEET: 1 OF 1	REV: M	

Tyco Electronics Corporation
 Harrisburg, PA 17105-3608
 AMP/PLMITE RCPT. FOR SOCKET CONTACTS
 HI DENSITY D CONNECTOR, SIZE 5, 78 POSN.,
 SERIES 90 WITH FLOAT BUSHINGS
 SIZE: A1 CAGE CODE: 00779 DRAWING NO: 204532
 CUSTOMER DRAWING