

Monitor - VL 19" LCD RTOUCH (S) FPM - 2400047

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



19-inch/48 cm flat panel LCD monitor with resistive touch screen. Includes two rear USB ports

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	1.000 g
Custom tariff number	85299020
Country of origin	Taiwan

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Display

Display	48.3 cm/19" TFT
Screen resolution	1280 x 1024 Pixel(s) (SXGA)
Backlighting	LED
Touch technology	Resistive industrial touch screen
Colors	16.7 million colors

Monitor data

Network	Without network
Slots	without slots

General

Mounting type	Front installation
Weight	9 g

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 55 °C

Monitor - VL 19" LCD RTOUCH (S) FPM - 2400047

Technical data

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (storage/transport)	5 % ... 95 %
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Device supply

Power supply unit	24 V DC ±20 %
-------------------	---------------

Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Classifications

eCl@ss

eCl@ss 5.1	27242402
eCl@ss 6.0	19200201
eCl@ss 8.0	19200403

ETIM

ETIM 3.0	EC001425
ETIM 4.0	EC001428
ETIM 5.0	EC001428

UNSPSC

UNSPSC 12.01	43211902
--------------	----------