

G2-LAURA-W-P

~45° wide beam. Assembly with thinner white holder, installation tape and location pins.


TECHNICAL SPECIFICATIONS:

Dimensions	21.6 x 21.6 mm
Height	13.1 mm
Fastening	tape, pin
Colour	white
Box size	450 x 260 x 160 mm
Box weight	6.1 kg
Quantity in Box	1440 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:



Component	Type	Material	Colour
LAURA-W	Lens	PMMA	clear
LAURA-LT-PIN-XP-HLD-WHT	Holder	PC	white
ROSE-TAPE	Tape	PU tape	black





PHOTOMETRIC DATA (MEASURED):





LED XB-D
 FWHM 40.0°
 Efficiency 84 %
 Peak intensity 1.600 cd/lm
 Required components:





LED XB-H
 FWHM 47.0°
 Efficiency 86 %
 Peak intensity 1.300 cd/lm
 Required components:



LED XP-E
 FWHM 45.0°
 Efficiency 86 %
 Peak intensity 1.500 cd/lm
 Required components:



LED XP-E2
 FWHM 45.0°
 Efficiency 87 %
 Peak intensity 1.500 cd/lm
 Required components:





PHOTOMETRIC DATA (MEASURED):

CREE 

LED XP-G
FWHM 46.0°
Efficiency 91 %
Peak intensity 1.550 cd/lm
Required components:



CREE 

LED XP-G2
FWHM 47.0°
Efficiency 87 %
Peak intensity 1.400 cd/lm
Required components:





CREE 

LED XP-L
FWHM 49.0°
Efficiency 85 %
Peak intensity 1.200 cd/lm
Required components:



CREE 



LED XP-L2
FWHM 46.0°
Efficiency 83 %
Peak intensity 1.300 cd/lm
Required components:





PHOTOMETRIC DATA (MEASURED):





LED XT-E
FWHM 43.0°
Efficiency 87 %
Peak intensity 1.600 cd/lm
Required components:





LED LUXEON 3030 2D
FWHM 37.0°
Efficiency 86 %
Peak intensity 1.900 cd/lm
Required components:



LED LUXEON TX
FWHM 42.0°
Efficiency 86 %
Peak intensity 1.600 cd/lm
Required components:





LED NCSxx19A
FWHM 41.0°
Efficiency 88 %
Peak intensity 1.700 cd/lm
Required components:




PHOTOMETRIC DATA (MEASURED):





LED NVSxx19A
FWHM 41.0°
Efficiency 87 %
Peak intensity 1.700 cd/lm
Required components:



LED NVSxx19B/NVSxx19C
FWHM 41.0°
Efficiency 84 %
Peak intensity 1.700 cd/lm
Required components:




LED Oslon Square EC
FWHM 46.0°
Efficiency 87 %
Peak intensity 1.400 cd/lm
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XHP35 HI
 FWHM 45.0°
 Efficiency 93 %
 Peak intensity 1.700 cd/lm
 Required components:





LED Oslon Black
 FWHM 41.0°
 Efficiency 95 %
 Peak intensity 2.300 cd/lm
 Required components:



LED Oslon Black Flat
 FWHM 34.0°
 Efficiency 94 %
 Peak intensity 2.900 cd/lm
 Required components:



LED Oslon Square Flat
 FWHM 41.0°
 Efficiency 94 %
 Peak intensity 2.150 cd/lm
 Required components:




PHOTOMETRIC DATA (SIMULATED):

OSRAM
Opto Semiconductors

LED SFH 4770S
FWHM 27.0°
Efficiency 93 %
Peak intensity cd/lm
Required components:

SEOL
SEOUL SEMICONDUCTOR

LED Z8Y22P
FWHM 40.0°
Efficiency 98 %
Peak intensity 2.150 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)