



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₁	REVISED	07/25/94	<i>AD</i>
B	PER EC 0U20-0116-01-05	19NOV01	<i>C. Hoang</i>

- NOTES:
1. CAPTURED CENTER CONTACT
 2. DIMENSION IS .006 (PIN RADIUS) + SUBSTRATE THICKNESS + SOLDER THICKNESS
 3. IF SLIDING CONTACTS ARE USED SEE AP48-008

.XXX = in
XX.X = mm

HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
BUSHING	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
SUPPORT BEAD	NORYL PPO EN265 COLOR: BLACK	N/A
CONTACT EXT. BUSHING	IRON-NICKEL ALLOY PER MIL-I-23011 CLASS 1 (KOVAR)	GOLD PLATE PER MIL-G-45204
HERMETIC SEAL	GLASS BEAD	N/A
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON		
FRAC. DEC. ANGLES ± 1/64 ± .005 ± °		
DRAWN BY <i>MC</i> DATE 4-14-92		
CHECKED BY <i>BB</i> 4/16/92		
APPD BY <i>CB</i> 4/16/92		
AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599		
TITLE OS-2.9 PANEL FEEDTHRU PLUG RECEPTACLE - FIELD REPLACEABLE		
SIZE B	CODE IDENT NO. 26805	4857-3578-02
SCALE 5:1		REV 01 ₁
SHEET 1 OF 1		

These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

USE ASSY PROCEDURE
408-04629
NO. AP (48-008)

CUSTOMER DRAWING

AMP PART # 1060034-1
SHEET 1 OF 1 REV B