



DESCRIPTION: 97 SERIES SOLDER STYLE PANEL & CABLE MOUNT
D-SUB CONNECTORS

MODEL NUMBER: 40-97XXS

APPLICATION: FOR CABLE

CRIMP TOOL: N/A



IMPEDANCE: N/A

FREQUENCY RANGE: 0-15 MHz

MATERIAL: HOUSING STEEL NICKEL PLATED
INSULATOR PBT+FIBER-GLASS UL94-V0 WHITE
CONTACT COPPER-ALLOY, GOLD PLATED

RoHS COMPLIANCE: YES

TECHNICAL DETAIL: N/A



DIM OUTLINE

MODEL NUMBER	PIN	A	B	C	D
40-9709S	09	30.80	24.99	16.30	19.20
40-9715S	15	39.15	33.32	24.65	27.70
40-9725S	25	53.00	47.04	38.40	41.10
40-9737S	37	69.30	63.50	54.80	57.30

<p>This PROPRIETARY Document is property of Cinch Connectivity Solutions. It is confidential in nature, non-transferable, and issued with the clear understanding that it is not traced or copied without permission and is returnable upon demand.</p> <p>INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.</p>	<p>3RD ANGLE PROJECTION</p>	<p>AIM-Cambridge</p>	
	<p>RoHS <input checked="" type="checkbox"/></p> <p>2002/95/EC</p>	<p>Title: D-Sub Connector, 97 Series, Solder Style Panel and Cable Mount, Female</p>	
<p>UNLESS OTHERWISE SPECIFIED UNITS: METRIC</p> <p>.XX ±.51</p> <p>.XXX ±.127</p> <p>ANGLES ±2°</p>	<p>Model No. 40-97XXS</p>		
<p>Size A</p>	<p>DO NOT SCALE DRAWING</p>	<p>Date: 9/9/2013</p>	<p>Sheet 1 of 1</p>