



- 1 HOUSING MATERIAL: GLASS-FILLED POLYMER.
- 2 POST MATERIAL: COPPER ALLOY.
- 3 POST FINISH: DIN 41612 CLASS 2 IN CONTACT AREA. TIN PLATE ON POSTS.
- 4 PART NUMBER, DATE CODE MARKED THIS APPROXIMATE AREA.
- 5 MARKING ON THIS SIDE.
- 6 RECOMMENDED HOLE SIZE FOR MANUAL APPLICATION OF CONNECTOR ONTO PC BOARD.
- CONTACT AREA FINISH: 0.00076 [0.00030] MIN GOLD OVER 0.00127 [0.00050] MIN NICKEL. TAIL FINISH: 0.0025 [0.00100] MIN MATTE TIN OVER 0.00127 [0.00050] MIN NICKEL.

SUPERSEDED BY 5650473-5	1-32	X	X	X	-	96	7-5650473-5
	1-32	X	X	X	7	96	5650473-6
	1-32	X	X	X	3	96	5650473-5
POSITIONS LOADED		C	B	A	FINISH	NO. OF LOADED POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN J. POLIGNONE DSMAYOS		APVD A. SHARPE DSMAYOS		NAME		ASSEMBLY, PIN EUROCARD, TYPE C, 96 POSITION, .104 SOLDER POST	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC		SIZE		SCALE	
0 PLC ± -		1 PLC ± -		2 PLC ± 0.13[.005]		3 PLC ± -		4 PLC ± -	
MATERIAL		FINISH		WEIGHT		DRAWING NO		RESTRICTED TO	
1/2		3		A1		00779 C=5650473		CUSTOMER DRAWING	
						SCALE 5:1		SHEET 1 OF 1	