



- 1 SEE TABLE FOR RIB QTY
- 2 THIS COUPLING SHROUD IS TO BE USED WITH AMPMODU MTE® RECEPTACLE ASSEMBLIES WITH GUIDE RIBS THE NUMBER OF POSITIONS LISTED EQUALS THE TOTAL NUMBER OF POSITIONS WHICH CAN BE CONTAINED WITHIN THE COUPLING SHROUD
- 3 FLAME RETARDANT THERMOPLASTIC, COLOR-BLACK.
- 4 PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.

4	1	.260	.485	6	1-103681-7
	2	2.460	2.685	50	1-103681-6
	2	1.960	2.185	40	1-103681-5
	2	1.660	1.885	34	1-103681-4
	2	1.560	1.785	32	1-103681-3
	2	1.460	1.685	30	1-103681-2
	2	1.360	1.585	28	1-103681-1
	2	1.260	1.485	26	1-103681-0
	2	1.160	1.385	24	103681-9
	2	1.060	1.285	22	103681-8
	2	.960	1.185	20	103681-7
	2	.860	1.085	18	103681-6
	1	.760	.985	16	103681-5
	1	.660	.885	14	103681-4
	1	.560	.785	12	103681-3
	1	.460	.685	10	103681-2
	1	.360	.585	8	103681-1
RIB QTY	C	A	NO OF POSN	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN H. MOLI 10-7-87
 CHK P. de JONG 10-7-87
 AMP Tyco Electronics Corporation Harrisburg, PA 17105

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC: 108-25034	NAME: COUPLING SHROUD, AMPMODU MTE, .100X.100 C/L, DOUBLE ROW
0 PLG ± -	1 PLG ± -	APPLICATION SPEC: 114-25026	SIZE: A1
2 PLG ± .005	3 PLG ± -	WEIGHT: -	CAGE CODE: 00779
4 PLG ± -	ANGLES ± -	MATERIAL: 3	DRAWING NO: 103681
FINISH: -		SCALE: 4:1	
CUSTOMER DRAWING		SHEET 1 OF 1 REV M	