

## Specification Sheet

Part Number: 151-00623



Standoff Bundling Clip, 2.2" Long, Panel Thickness .03"–.22", PA66HIRHS, Black, 1500/box

|                     |  |
|---------------------|--|
| Article Number      | 151-00623  |
| Type                | SOCHFT6  |
| Color               | Black (BK)   |
| Features & Benefits | <ul style="list-style-type: none"><li>•Clip can be installed by hand – no need for hardware or tools.</li><li>•Design provides low insertion and high extraction force, for simple, secure performance.</li><li>•Clip keeps bundle away from areas that could cause damage due to rubbing.</li></ul> |
| Quantity Per        | box  |

### Product Description

Standoff bundling clips provide a straightforward way to secure cable bundles, hoses or pipes. The bundle fastens to the tape bar using tape or cable ties. Multiple orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standoff keeps bundles away from mounting area to prevent them from damage due to rubbing.

|  |  |
|--|--|
| <b>Short Description</b>                       | Standoff Bundling Clip, 2.2" Long, Panel Thickness .03"-.22", PA66HIRHS, Black, 1500/box |
| <b>Global Part Name</b>                        | SOCHFT6-PA66HIRHSUV-BK   |
| <b>Length L (Imperial)</b>                     | 2.2  |
| <b>Length L (Metric)</b>                       | 56.0   |
| <b>Offset Length(Imperial)</b>                 | 1.22   |
| <b>Offset Length(Metric)</b>                   | 31.0   |
| <b>Fixation Method</b>                         | Fir Tree   |
| <b>Height H (Imperial)</b>                     | 0.9  |
| <b>Height H (Metric)</b>                       | 22.5   |
| <b>Panel Thickness Min(Imperial)</b>           | 0.03   |
| <b>Panel Thickness Max(Imperial)</b>           | 0.22   |
| <b>Panel Thickness Min (Metric)</b>            | 0.76   |
| <b>Panel Thickness Max (Metric)</b>            | 5.59   |
| <b>Mounting Hole Diameter D (Imperial)</b>     | 0.25 - 0.27  |
| <b>Mounting Hole Diameter D (Metric)</b>       | 6.35 - 7.0 mm  |
| <b>Mounting Hole Diameter D Min (Imperial)</b> | 0.27   |

|  |  |
|--|--|
| <b>Mounting Hole Diameter D Max (Imperial)</b> | 0.28   |
| <b>Mounting Hole Diameter D Max (Metric)</b>   | 7.0  |
| <b>Material</b>                                | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| <b>Material Shortcut</b>                       | PA66HIRHSUV  |
| <b>Flammability</b>                            | UL 94 HB   |
| <b>Operating Temperature (Metric)</b>          | -40°F to +230°F (-40°C to +110°C)  |
| <b>Reach Complaint(Article 33)</b>             | Yes  |
| <b>Package Quantity(Imperial)</b>              | 1500   |
| <b>Package Quantity (Metric)</b>               | 1500   |
| <b>Customs Number</b>                          | 3926909987   |
| <b>Content Unit(BMEcat)</b>                    | pcs.   |