

SUMMARY

Wires

Low	3
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0



Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

Series

Termination type	Male crimp
IP rating	68
Cable Ø	7.60 - 8.00 mm
Matching parts	EGG.3K.303.CYM
Status	
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FG*: Straight plug, cable adapter and nut for fitting a bend relief
Keying	1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	∅ 7.6 - 8 mm
Variant	Z : Nut for fitting a bend relief

Performance

Configuration	3K.303 : 3 Low Voltage
Insulator	Y: PEEK for crimp contacts
Rated Current	25 Amps

Specifications

Contact Type: Crimp
Max. Matings: 5000
Contact Retention: 65 N
Contact Dia.: 2 mm (0.079in)
Bucket Dia.: 2.4 mm (0.094in)
Min. Conductor: 1.5 mm ² (AWG 16)


Max. Conductor: 2.5 mm² (AWG 12)
 R (max): 3.3 mOhm
 Vtest (contact-shell): 2650 V (AC), 3750 V (DC)
 Vtest (contact-contact): 3200 V (AC), 4530 V (DC)

Others

Humidity (max): ≤95% [at 60 deg C / 140 F]
 Vibration: 15 g [10 Hz - 2000 Hz]
 Shock Resistance: 100 g [6 ms]
 Salt Spray Corrosion: >1000 hr
 Climatological Category: 50/175/21
 Shielding (min): 95 dB (10 MHz)
 Shielding (min): 80 dB (1 GHz)
 IP Rating: 68

DRAWINGS

Draws



Dimensions

	A	L	M	S2
mm.	19	60	40	15
in.	0,75	2,36	1,57	0,59


RECOMMENDED BY LEMO

Tools

Crimp Tool: DPC.91.101.A
 Crimp settings: AWG/Selector = 12-14-16/7-6-5
 Positionner: DCE.91.203.BVCM

Extractor: DCC.91.202.5LA
Replacement contact: FGG.3B.575.ZZC
Spanner wrench: DCD.3E.030.PA150
Caps: BFG.3K.100.NAS

Cables

CMN.03.T14.078PGCE			
330 150	PVC	Grey	