

## Base strip - MC 1,5/20-G-3,5-RN - 1731853

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 20, Pitch: 3.5 mm, Color: green, Contact surface: Tin, Assembly: Soldering



The figure shows a 10-position version of the product



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 pc      |
| Minimum order quantity               | 50 pc     |
| Weight per Piece (excluding packing) | 21.64 GRM |
| Custom tariff number                 | 85366990  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|                |              |
|----------------|--------------|
| Length         | 9.2 mm       |
| Pitch          | 3.5 mm       |
| Dimension a    | 66.5 mm      |
| Pin dimensions | 0,8 x 0,8 mm |
| Hole diameter  | 1.2 mm       |

#### General

|                             |                 |
|-----------------------------|-----------------|
| Range of articles           | MC 1,5/...-G-RN |
| Insulating material group   | IIIa            |
| Rated surge voltage (III/3) | 2.5 kV          |
| Rated surge voltage (III/2) | 2.5 kV          |
| Rated surge voltage (II/2)  | 2.5 kV          |
| Rated voltage (III/3)       | 160 V           |
| Rated voltage (III/2)       | 160 V           |

## Base strip - MC 1,5/20-G-3,5-RN - 1731853

### Technical data

#### General

|   |        |
|---|--------|
| Rated voltage (U/2)                     | 250 V  |
| Connection in acc. with standard        | EN-VDE |
| Nominal current I <sub>N</sub>          | 8 A    |
| Maximum load current                    | 8 A    |
| Insulating material                     | PBT    |
| Inflammability class according to UL 94 | V0     |
| Color                                   | green  |
| Number of positions                     | 20     |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / UL Recognized / cUL Recognized / cULus Recognized


# Base strip - MC 1,5/20-G-3,5-RN - 1731853


## Approvals


Ex Approvals


Approvals submitted

### Approval details

|   |       |       |
|---|-------|-------|
| UL Recognized  |       |       |
|   | B     | D     |
| Nominal current IN  | 8 A   | 8 A   |
| Nominal voltage UN  | 300 V | 300 V |

|  |       |       |
|--|-------|-------|
| cUL Recognized  |       |       |
|  | B     | D     |
| Nominal current IN   | 8 A   | 8 A   |
| Nominal voltage UN   | 300 V | 300 V |

|   |       |       |
|---|-------|-------|
| UL Recognized  |       |       |
|   | B     | D     |
| Nominal current IN  | 8 A   | 8 A   |
| Nominal voltage UN  | 300 V | 300 V |

|  |       |       |
|--|-------|-------|
| cUL Recognized  |       |       |
|  | B     | D     |
| Nominal current IN   | 8 A   | 8 A   |
| Nominal voltage UN   | 300 V | 300 V |


# Base strip - MC 1,5/20-G-3,5-RN - 1731853

## Approvals



## Drawings

Drilling diagram



Dimensioned drawing

