

# Patch panels - VS-PP-F-RJ45-CAT6 - 1658118


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Patch panel, RJ45, DIN rail mounting, IP20, 1 slot, IDC connection, CAT6



## Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 326 (PC-2011)
GTIN	 4 046356 149174
Custom tariff number	85366990
Country of origin	SWITZERLAND

## Technical data

### Mechanical characteristics

Number of positions	8
Number of slots	1
Shielded	Yes
Insertion/withdrawal cycles	≥ 750
Connection method	IDC fast connection
Conductor cross section	0.2 mm <sup>2</sup> ... 0.32 mm <sup>2</sup>
Connection cross section AWG	24 ... 22
External cable diameter	4.5 mm ... 8 mm
Color	gray
Ambient temperature (operation)	-10 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

### Material data

Inflammability class according to UL 94	V0
Housing material	PC-GF
Contact carrier material	PC
Contact material	Copper alloy
Contact surface material	Gold over nickel

# Patch panels - VS-PP-F-RJ45-CAT6 - 1658118

## Technical data

### Material data

Degree of protection	IP20
----------------------	------

### Electrical characteristics

Number of positions	8
Transmission characteristics (category)	CAT6
Rated current	1 A

## Classifications

### eclass

eCl@ss 4.0	272607XX
eCl@ss 4.1	27260701
eCl@ss 5.0	19030109
eCl@ss 5.1	19030109
eCl@ss 6.0	19170107
eCl@ss 7.0	19170112

### etim


ETIM 3.0	EC001128
ETIM 4.0	EC001128

### unspsc

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## Drawings

### Dimensioned drawing



RJ45 patch panel