

| COUNT   | DESCRIPTION OF REVISIONS    | BY   | CHKD   | DATE   | COUNT  | DESCRIPTION OF REVISIONS        | BY                              | CHKD                                 | DATE            |
|---|-----------------------------|--|--------|--------|--|---------------------------------|---------------------------------|--------------------------------------|-----------------|
| △   |                             |  |        |        | △  |                                 |                                 |                                      |                 |
| △   |                             |  |        |        | △  |                                 |                                 |                                      |                 |
| <b>APPLICABLE STANDARD</b>  |                             |  |        |        |  |                                 |                                 |                                      |                 |
| <b>RATING</b>   | OPERATING TEMPERATURE RANGE | -30 °C TO +85 °C(NOTE1)  |        |        | STRAGE TEMPERATURE RANGE   | -10 °C TO +60 °C(NOTE2)         |                                 |                                      |                 |
|   | OPERATING HUMIDITY RANGE    | 20 % TO 80 %   |        |        | STRAGE HUMIDITY RANGE  | 40 % TO 70 % (NOTE2)            |                                 |                                      |                 |
|   | VOLTAGE                     | 250 V AC   | UL.CSA | 30V AC |  |                                 |                                 |                                      |                 |
|   | CURRENT                     | 2 A  |        | 2A     |  |                                 |                                 |                                      |                 |
| <b>SPECIFICATIONS</b>   |                             |  |        |        |  |                                 |                                 |                                      |                 |
| <b>ITEM</b>   |                             | <b>TEST METHOD</b>   |        |        | <b>REQUIREMENTS</b>  |                                 |                                 | <b>QT</b>                            | <b>AT</b>       |
| <b>CONSTRUCTION</b>   |                             |  |        |        |  |                                 |                                 |                                      |                 |
| GENERAL EXAMINATION   |                             | VISUALLY AND BY MEASURING INSTRUMENT.  |        |        | ACCORDING TO DRAWING.  |                                 |                                 | ×                                    | ×               |
| MARKING   |                             | CONFIRMED VISUALLY.  |        |        |  |                                 |                                 | ×                                    | ×               |
| <b>ELECTRIC CHARACTERISTICS</b>   |                             |  |        |        |  |                                 |                                 |                                      |                 |
| CONTACT RESISTANCE  |                             | 100 mA (DC OR 1000 Hz).  |        |        | 30 mΩ MAX.   |                                 |                                 | ×                                    | —               |
| INSULATION RESISTANCE   |                             | 500 V DC.  |        |        | 1000 MΩ MIN.   |                                 |                                 | ×                                    | —               |
| VOLTAGE PROOF   |                             | 650 V AC FOR 1 min.  |        |        | NO FLASHOVER OR BREAKDOWN.   |                                 |                                 | ×                                    | —               |
| <b>MECHANICAL CHARACTERISTICS</b>   |                             |  |        |        |  |                                 |                                 |                                      |                 |
| MECHANICAL OPERATION  |                             | 50 TIMES INSERTIONS AND EXTRACTIONS.   |        |        | ① CONTACT RESISTANCE: 30 mΩ MAX.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.  |                                 |                                 | ×                                    | —               |
| VIBRATION   |                             | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.   |        |        | ① NO ELECTRICAL DISCONTINUITY OF 1 μs.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.                                    |                                 |                                 | ×                                    | —               |
| SHOCK   |                             | 490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.  |        |        |  |                                 |                                 | ×                                    | —               |
| <b>ENVIRONMENTAL CHARACTERISTICS</b>  |                             |  |        |        |  |                                 |                                 |                                      |                 |
| RAPID CHANGE OF TEMPERATURE   |                             | TEMPERATURE -55→5 TO 35→+85→5 TO 35°C<br>TIME 30→5 TO 15→ 30→5 TO 15min<br>UNDER 5 CYCLES.   |        |        | ① CONTACT RESISTANCE: 30 mΩ MAX.<br>② INSULATION RESISTANCE: 1000 MΩ MIN.<br>③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. |                                 |                                 | ×                                    | —               |
| DAMP HEAT (STEADY STATE)  |                             | EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.  |        |        | ① CONTACT RESISTANCE: 30 mΩ MAX.<br>② INSULATION RESISTANCE: 500 MΩ MIN.<br>③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.  |                                 |                                 | ×                                    | —               |
| RESISTANCE TO SOLDERING HEAT  |                             | 1) AUTOMATIC SOLDERING (REFLOW)<br>《REFLOW AREA》<br>MAX 240°C WITHIN 10 s<br>MIN 220°C WITHIN 30 s<br>《PREHEATING AREA》<br>150°C 100 TO 120 s<br>PUT THROUGH IN REFLOW FUMACE TWICE.<br>LEAVE IN AMBIENT TEMPERATURE AND HUMIDITY FOR 1 HOUR. CONNECTOR TEMPERATURE TO BE AMBIENT FOR SECOND REFLOW.<br>2) MANUAL SOLDERING<br>SOLDERING IRON TEMPERATURE : 290±10°C,<br>SOLDERING TIME : 3 s<br>NO STRENGTH ON CONTACT. |        |        | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.  |                                 |                                 | ×                                    | —               |
| SOLDERABILITY   |                             | SOLDERING TEMPERATURE : 230±5°C<br>SOLDERING TIME : 3 s  |        |        | A NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.                             |                                 |                                 | ×                                    | —               |
| <b>REMARKS</b>  |                             |  |        |        | <b>DRAWN</b>   | <b>DESIGNED</b>                 | <b>CHECKED</b>                  | <b>APPROVED</b>                      | <b>RELEASED</b> |
| NOTE1:INCLUDING THE TEMPERATURE RISE BY CURRENT.<br>NOTE2:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD, AFTER PCB BOARD,OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.<br>Unless otherwise specified, refer to JIS C 5402. |                             |  |        |        | F.Matsuki<br>'04.12.28   | <i>J. Dempouya</i><br>'04.12.28 | <i>T. Miyazaki</i><br>'04.12.28 | <i>T. Miyazaki</i><br>'04.12.28      |                 |
| Note QT:Qualification Test AT:Assurance Test ×:Applicable Test  |                             |  |        |        |  |                                 |                                 |                                      |                 |
| <b>HRS HIROSE ELECTRIC CO., LTD.</b>  |                             |  |        |        | <b>SPECIFICATION SHEET</b>   |                                 |                                 | PART NO.<br><b>DF11G-*DP-2V (50)</b> |                 |
| CODE NO.(OLD)<br><b>CL</b>  |                             | DRAWING NO.<br><b>ELC4-162244-02</b>   |        |        | PART NO.<br><b>CL543</b>   |                                 |                                 | 1<br>1                               |                 |

|    |
|----|
| TO |
|    |
|    |
|    |

