



## Ethernet Media converter Ha-VIS eCon 3011-ASFP

2-port Ethernet Media converter for vertical installation in control cabinets,  
including 1 F.O. port (SFP)

Unmanaged	IP30	PROFINET compatible <input checked="" type="checkbox"/>	EtherNet/IP compatible <input checked="" type="checkbox"/>
-----------	------	---	--

Number of ports, Copper / Termination 1x 10/100Base-T(X) / RJ45 (Twisted Pair)

Number of ports, F.O. / Termination 1x 100Base-FX / SFP module slot

### mode PoE

Input voltage / Termination 48 V DC  
 Permissible range (min./max.) 46 V ... 57 V DC  
 Input current approx. 100 mA ... 400 mA at 48 V DC with PoE

### mode Non-PoE

Input voltage / Termination 24 V DC / 5-pole, pluggable screw contact, redundant  
 (PWR1 + / PWR1 - / PWR2 + / PWR2 - / FE)  
 Permissible range (min./max.) 12 V ... 30 V DC  
 Input current approx. 100 mA (at 24 V DC)

Housing material metal, powder-coated  
 Dimensions (W x H x D) 23 x 130 x 100 mm (without connectors)  
 Weight approx. 0.6 kg  
 Working temperature -40 °C ... +70 °C  
 Approvals cUL (in preparation)  
 MTBF 2.090.000 h

Identification	Part number	Drawing	Dimensions in mm
----------------	-------------	---------	------------------

Ha-VIS eCon 3011-ASFP  
 Ethernet Switch with  
 1 RJ45 port  
 1 F.O. port

20 76 102 3101

