



Part Number: 8899

Test Prod Wire, (1) 18 AWG (65x36) TC, Rubber

[Request Sample](#)

Product Description

One 18 AWG stranded (65x36) tinned copper conductor, rubber insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
18	65x36	TC - Tinned Copper	1

Conductor Count:	1
Conductor Size:	18 AWG

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
Rubber	0.144 in	0.0485 in

Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.144 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
6.5 Ohm/1000ft

Shielding:	Unshielded
------------	------------

Current

Element	Max. Recommended Current [A]
10C temperature rise	10C temperature rise 8 amps @ 25C ambient

Voltage

Breakdown Voltage	Suggested Working Voltage
20,000 V RMS	5000 V RMS

Temperature Range

Operating Temp Range:	-40°C To +90°C
-----------------------	----------------

Mechanical Characteristics

Bulk Cable Weight:	15 lbs/1000ft
--------------------	---------------

Standards

UL AWM Style:	N/A
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
--------------------------------	-----

EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A
--------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
8899 010100	Black	
8899 0101000	Black	C
8899 01025	Black	
8899 010500	Black	
8899 010U1000	Black	
8899 010U500	Black	
8899 006100	Blue, Light	
8899 006500	Blue, Light	
8899 005100	Green, Dark	
8899 005500	Green, Dark	
8899 002100	Red	
8899 0021000	Red	C
8899 00225	Red	
8899 002500	Red	
8899 002U1000	Red	
8899 002U500	Red	
8899 009100	White	
8899 009500	White	
8899 004100	Yellow	
8899 004500	Yellow	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.