

APPROVED BY _____



COMPANY: _____

PURCHASING/ENGINEER: _____

DATE: _____

P/N	L	T
P556-003	3FT	±1.18"
P556-006	6FT	±2"
P556-009	9FT	±2"
P556-010	10FT	±2"
P556-012	12FT	±2"
P556-015	15FT	+6"/-2"
P556-025	25FT	+6"/-2"

WIRE LIST:



NOTE:

- CABLE:UL20276 (30AWG+B+JACKET)*3COAX+28AWG*1P+28AWG*5C+AL +DRAIN(BARE COPPER)+BRAID(65% AL),PVC JACKET:BLACK OD=0.276"±0.006"(OD=7.0i±0.15MM).
- CONNECTOR: P1 DVI 12+5 MALE,PIN:G/F,INSULATION BLACK. P2 HDB15M,PIN:G/F,INSULATION BLACK.
- SCREW:#4-40UNC P1:MOLDED WHITE. P2:MOLDED 661C BLUE.
- HOOD MOLDED:P1: 45P PVC WHITE. P2: 45P PVC 661C BLUE .
- FERRITE CORE:ø17.5*28.5*9.5MM MOLDED BLACK.
- MOLD NO:P1: DVI-01, FC-01, HD15-01.



B	UPDATE DRAWING		12/13/11				
A	INITIAL RELEASE		08/30/06				
REV	DESCRIPTION OF CHANGE		DATE				
TOLERANCE		TRIPP-LITE					
INCHES							
M/M							
.X	.015	.30	SCALE	NONE	⊕	REV	B
.XX	.010	.10	UNIT	MM			
.XXX	.005	.05					
DRAWN BY	Tiger		SHEET	1/1	DWG NO.		
			DATE	12/13/11			
CHECK BY			TITLE				
			DVI12+5/M TO HDB15/M				
APPD BY			PART NO.				
			P556-XXX				