

## Bus system cable - VS-FSDBPS-OE-93K-LI/0,5 - 1419154

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Assembled Sercos III cable, shielded, star quad, AWG 22 stranded (7-wire), RAL 3020 (traffic red), M12 flush-type socket, rear mounting, SPEEDCON 4-pos. on free conductor end, length: 0.5 m



### Key commercial data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85444290 |
| Country of origin    | Germany  |

### Technical data

#### Dimensions

|                 |       |
|-----------------|-------|
| Length of cable | 0.5 m |
|-----------------|-------|

#### Ambient conditions

|                      |      |
|----------------------|------|
| Degree of protection | IP67 |
|----------------------|------|

#### General data

|                        |            |
|------------------------|------------|
| Rated current at 40°C  | 4 A        |
| Rated voltage          | 250 V      |
| Number of positions    | 4          |
| Signal type/category   | Sercos III |
| Surge voltage category | II         |
| Pollution degree       | 3          |

#### Characteristics head 1

|  |   |
|--|---|
| Head type                                | Flush-type socket Straight M12 SPEEDCON |
| No. of positions (pin connector pattern) | 4                                       |

#### Characteristics head 2

|           |                |
|-----------|----------------|
| Head type | free cable end |
|-----------|----------------|

## Bus system cable - VS-FSDBPS-OE-93K-LI/0,5 - 1419154

### Technical data

#### Characteristics head 2

|  |   |
|--|---|
| No. of positions (pin connector pattern) | 4 |
|--|---|

#### Cable

|   |  |
|---|--|
| Cable type                                    | Sercos III   |
| Cable type (abbreviation)                     | 93K  |
| UL AWM style                                  | 21694 (60°C / 600 V)   |
| Signal type/category                          | Sercos III CAT5 (IEC 11801:2002), 100 Mbps<br>Sercos III CAT5e (TIA 568B:2001), 100 Mbps |
| Cable structure                               | 1x4xAWG22/7; SF/TQ   |
| Conductor cross section                       | 4x 0.34 mm <sup>2</sup>  |
| AWG signal line                               | 22   |
| Conductor structure signal line               | 7x 0.25 mm   |
| Core diameter including insulation            | approx. 1.55 mm  |
| Wire colors                                   | White, yellow, blue, orange  |
| Type of pair shielding                        | Aluminum-lined polyester foil  |
| Overall twist                                 | Star quad  |
| Shielding                                     | Tinned copper braided shield   |
| External sheath, color                        | signal red RAL 3020  |
| Outer sheath thickness                        | approx. 0.9 mm   |
| External cable diameter D                     | 6.5 mm ±0.2 mm   |
| Minimum bending radius, fixed installation    | 3 x D  |
| Minimum bending radius, flexible installation | 7 x D  |
| Cable weight                                  | 68 kg/km   |
| Outer sheath, material                        | PVC  |
| Material, inner sheath                        | PVC  |
| Material conductor insulation                 | PE   |
| Conductor material                            | Tin-plated Cu litz wires   |
| Insulation resistance                         | ≥ 0.5 GΩ*km  |
| Conductor resistance                          | ≤ 120 Ω/km   |
| Wave impedance                                | 100 Ω ±15 Ω (at 100 MHz)   |
| Signal runtime                                | 5.3 ns/m   |
| Coupling resistance                           | ≤ 20.00 mΩ/m (at 10 Hz)  |
| Test voltage Core/Core                        | 2000 V (50 Hz, 1 min.)   |
| Test voltage Core/Shield                      | 2000 V (50 Hz, 1 min.)   |
| Flame resistance                              | According to UL 1685 (CSA FT 4)  |
| Resistance to oil                             | Resistant to oil to a limited extent   |
| Other resistance                              | UV resistant According to UL 1581, Section 1200  |
| Ambient temperature (operation)               | -40 °C ... 70 °C (cable, fixed installation)   |

## Bus system cable - VS-FSDBPS-OE-93K-LI/0,5 - 1419154

### Technical data

#### Cable

|   |   |
|---|---|
|   | -40 °C ... 70 °C (cable, flexible installation) |
| Ambient temperature (installation)      | -20 °C ... 60 °C                                |
| Ambient temperature (storage/transport) | -50 °C ... 70 °C                                |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060307 |
| eCl@ss 4.1 | 27060307 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 5.1 | 27060307 |
| eCl@ss 6.0 | 27279218 |
| eCl@ss 7.0 | 27279218 |
| eCl@ss 8.0 | 27279218 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000830 |
| ETIM 3.0 | EC000830 |
| ETIM 4.0 | EC002599 |
| ETIM 5.0 | EC000830 |


#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 26121616 |
| UNSPSC 7.0901 | 26121616 |
| UNSPSC 11     | 26121604 |
| UNSPSC 12.01  | 26121616 |
| UNSPSC 13.2   | 26121616 |

### Drawings

## Bus system cable - VS-FSDBPS-OE-93K-LI/0,5 - 1419154

Dimensioned drawing




Housing cutout for Pg9 fastening thread, mounting panel with feed-through hole (alternatively with surface as protection against rotation)

Cable cross section



Sercos III [93K]

Dimensioned drawing



M12 panel feed-through