

## PCB terminal block - ZFKDSA 2,5-6,08 R-EX - 1732153

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Nominal current (Ex): 22 A, Nominal voltage (Ex): 125 V, Pitch: 5.08 mm, Number of positions: 1, Connection method: Spring-cage connection, Mounting: Soldering, Color: green

### Product Features

- Desk shape with a clear delimitation of the conductor entry and the actuation opening (screwdriver shaft)
- Compact housing dimensions
- Two solder pins for a high level of stability on the PCB
- Modular design enables blocking for larger numbers of positions
- PCB single terminal block with spring-cage connection

### Key commercial data

Packing unit	1 pc
Minimum order quantity	50 pc
Custom tariff number	85369010
Country of origin	Poland

### Technical data

#### Dimensions

Pitch	5.08 mm
Pin dimensions	0,8 x 0,8
Hole diameter	1.3 mm

#### General

Range of articles	ZFKDS(A) 2,5-EX
Nominal cross section	2.5 mm <sup>2</sup>
Insulating material	PA
Solder pin surface	Sn
Number of positions	1

### Classifications

#### eCl@ss

eCl@ss 4.0	27141111
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190

## PCB terminal block - ZFKDSA 2,5-6,08 R-EX - 1732153

### Classifications

#### eCl@ss

eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401
eCl@ss 8.0	27440401

#### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

#### UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432