

## Base strip - MCV 1,5/ 6-GFR-3,81 P26 THR - 1707793

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 6, Pitch: 3.81 mm, Color: black, Contact surface: Tin, Assembly: SMD/THT/THR, User information and design recommendations for through hole reflow technology can be found under "Downloads"



The illustration shows the 10-position version



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 2.19 GRM |
| Custom tariff number                 | 85366990 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                |              |
|----------------|--------------|
| Length         | 7.25 mm      |
| Height         | 9.2 mm       |
| Pitch          | 3.81 mm      |
| Dimension a    | 19.05 mm     |
| Pin dimensions | 0,8 x 0,8 mm |
| Pin spacing    | 3.81 mm      |
| Hole diameter  | 1.3 mm       |

#### General

|                             |                    |
|-----------------------------|--------------------|
| Range of articles           | MCV 1,5/..-GFR-THR |
| Insulating material group   | IIIa               |
| Rated surge voltage (III/3) | 2.5 kV             |
| Rated surge voltage (III/2) | 2.5 kV             |
| Rated surge voltage (II/2)  | 2.5 kV             |

## Base strip - MCV 1,5/ 6-GFR-3,81 P26 THR - 1707793

### Technical data

#### General

|   |                    |
|---|--------------------|
| Rated voltage (III/3)                   | 160 V              |
| Rated voltage (III/2)                   | 160 V              |
| Rated voltage (II/2)                    | 250 V              |
| Connection in acc. with standard        | EN-VDE             |
| Nominal current I <sub>N</sub>          | 8 A                |
| Maximum load current                    | 8 A (per position) |
| Insulating material                     | LCP                |
| Inflammability class according to UL 94 | V0                 |
| Color                                   | black              |
| Number of positions                     | 6                  |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

### Approvals

#### Approvals

---

# Base strip - MCV 1,5/ 6-GFR-3,81 P26 THR - 1707793

## Approvals

Approvals

UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized

Ex Approvals

Approvals submitted

## Approval details

|                                |       |       |
|--------------------------------|-------|-------|
| UL Recognized                  |       |       |
|                                | B     | D     |
| Nominal current I <sub>N</sub> | 8 A   | 8 A   |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

|                                |       |       |
|--------------------------------|-------|-------|
| cUL Recognized                 |       |       |
|                                | B     | D     |
| Nominal current I <sub>N</sub> | 8 A   | 8 A   |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

|      |  |  |
|------|--|--|
| GOST |  |  |
|------|--|--|


|      |  |  |
|------|--|--|
| GOST |  |  |
|------|--|--|

|                  |  |  |
|------------------|--|--|
| cULus Recognized |  |  |
|------------------|--|--|

## Drawings

# Base strip - MCV 1,5/ 6-GFR-3,81 P26 THR - 1707793

Drilling diagram



Dimensioned drawing

