

Aug.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

| | | | | |
|---------------------|-----------------------------|---|---------------------------|---------------------------------|
| Applicable standard | | MIL-STD-348B | | |
| Rating | Operating temperature range | Δ -55 °C to +125 °C (95 %RH Max.) | Storage temperature range | -20 °C to +70 °C (90 %RH Max.) |
| | Power | -- W | Characteristic impedance | 50 Ω (0 to 30 GHz) |
| | Peculiarity | ---- | Applicable cable | ---- |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|---------------------|---------------------------------------|-----------------------|----|----|
| CONSTRUCTION | | | | |
| General examination | Visually and by measuring instrument. | According to drawing. | X | X |
| Marking | Confirmed visually. | | - | - |

| ELECTRICAL CHARACTERISTICS | | | | | |
|-----------------------------------|---|----------------------------|-------------------|---|---|
| Contact resistance | 100 mA (DC or 1000 Hz) | Center contact | 6 m Ω Max. | X | X |
| | | Outer contact | 6 m Ω Max. | X | X |
| Insulation resistance | 500 V DC. | 1000 M Ω Min. | | X | X |
| Withstanding voltage | 500 V AC for 1 min. current leakage 2 mA Max. | No flashover or breakdown. | | X | X |
| V.S.W.R. | Frequency 0 to 30 GHz. | V.S.W.R. | 1.5 Max. | X | - |
| Insertion loss | Frequency - to - GHz. | --- dB Max. | | - | - |

| MECHANICAL CHARACTERISTICS | | | | | |
|---|---|--|------------|---|---|
| Contact insertion and extraction forces | ϕ --- by steel gauge. | Insertion force | --- N Max. | - | - |
| | | Extraction force | --- N Min. | - | - |
| Insertion and extraction forces | Measured by applicable connector. [SMPJ-HKJ] | Insertion force | 18 N Max. | X | X |
| | | Extraction force | 2.2 N Min. | X | X |
| Mechanical operation | 1000 times insertion and extractions. | 1)Contact resistance: Center contact 12 m Ω Max. Outer contact 12 m Ω Max. | | X | - |
| | | 2)No damage, crack and looseness of parts. | | | |
| Vibration | Frequency 10 to 500 Hz single amplitude 0.75 mm, 98 m/s ² at 10 cycles for 3 directions. | 1)No electrical discontinuity of 1 μ s. | | X | - |
| | | 2)No damage, crack and looseness of parts. | | | |
| Shock | 490 m/s ² directions of pulse 11 ms at 3 times for 3 directions. | | | X | - |
| | | | | | |
| Cable clamp strength (against cable pull) | Using a pulling tester, pull the cable axially at a rate of --- mm/min. and record the strength at which the cable or connector breaks. | --- N Min. | | - | - |

| ENVIRONMENTAL CHARACTERISTICS | | | | | |
|--------------------------------------|---|---|------------------------|---|---|
| Temp heat | Exposed at +25 to +65 °C, 90 to 98 % total 10 cycles. (240 h) | 1)Insulation resistance: 100 M Ω Min. (at high humidity) | | X | - |
| | | 2) Insulation resistance: 1000 M Ω Min. (at dry) | | | |
| | | 3)No damage, crack and looseness of parts. | | | |
| Rapid change of temperature | Temperature -55 \rightarrow - \rightarrow +125 \rightarrow - °C Time 30 \rightarrow 3 \rightarrow 30 \rightarrow 3 min. Under 5 cycles. | No damage, crack and looseness of parts. | | X | - |
| Corrosion salt mist | Exposed in 5 % salt water spray for 48 h. | V.S.W.R. | 1.5 Max. [0 to 30 GHz] | X | - |

| | | | | |
|------------|--------------------------|--------------|------------|----------|
| Count | Description of revisions | Designed | Checked | Date |
| Δ 1 | DIS-D-00003210 | TK.SAWAGUCHI | KY.SHIMIZU | 18.06.07 |

| | | | |
|--|----------|--------------|----------|
| Remark RoHS COMPLIANT Note \square The characteristic after mounting on the board. | Approved | TO.KATAYAMA | 18.03.20 |
| | Checked | KY.SHIMIZU | 18.03.20 |
| | Designed | TK.SAWAGUCHI | 18.03.19 |
| | Drawn | TK.SAWAGUCHI | 18.03.19 |

Unless otherwise specified, refer to IEC 60512.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

| | | | |
|------------|---------------------------|----------|---|
| HRS | SPECIFICATION SHEET | Part No. | ELC-373489-01-00 |
| | HIROSE ELECTRIC CO., LTD. | Code No. | SMP-PR(SB)-SMT-1(01) CL338-1104-0-01 |