

| Δ | COUNT | REVISIONS | BY | CHKD | DATE | Δ | COUNT | REVISIONS | BY | CHKD | DATE |
|---|-------|-----------|----|------|------|---|-------|-----------|----|------|------|
| Δ | | | | | | Δ | | | | | |
| Δ | | | | | | Δ | | | | | |

| | | | | | | |
|---------------------|-----------|-------------------|---|----------|-----------------------------|-------------------------|
| APPLICABLE STANDARD | | CONTACT No. / ~ * | | AC 250 V | APPLICABLE CABLES | |
| RATING | VOLTAGE | DC | V | 3 A | IMPEDANCE FREQUENCY RANGE | Ω (0 ~ Hz) |
| | CURRENT | CONTACT No. / ~ * | | 3 A | OPERATING TEMPERATURE RANGE | -35°C ~ +85°C (Notes:1) |
| | POWER | | | | | |
| | SPECIALTY | | | | | |

SPECIFICATIONS

| No. | ITEM | CONDITIONS | TEST STANDARD | MIN | MAX | UNITS | QT. | AT |
|-----|--|--|---------------|------|-----|-------|-----|----|
| 1 | DESIGN-MATERIAL-FINISH | ADC Applicable std. and DC 3-160092-02 | | - | - | - | ○ | ○ |
| 2 | MARKING | | | - | - | - | ○ | ○ |
| 3 | INSULATION RESISTANCE | Must be over standard value at DC 500V. | MIL-STD-1344 | 1000 | - | MΩ | ○ | - |
| 4 | CONTACT RESISTANCE | The voltage drop must be under the std. value at DC 0.1 A. | MIL-STD-1344 | - | 30 | mΩ | ○ | - |
| | UNIT CONTACT CONTACT | The voltage drop must be under the std. value at DC A. | | - | - | mΩ | - | - |
| 5 | DIELECTRIC WITHSTANDING VOLTAGE | Must withstand AC 650V for one minute. | MIL-STD-1344 | - | - | - | ○ | - |
| 6 | LOW LEVEL CIRCUIT | The Contact Resistance must be under the std. value at DC 20mV less and mA. | | - | - | mΩ | - | - |
| 7 | DRY CIRCUIT | Must have conductivity in alternate current at DC μV. | | - | - | - | - | - |
| 8 | CONTACT ENGAGEMENT AND SEPARATION FORCES | Must be suitable for the std. gauge size value at applicable gauge. | | - | - | gf | - | - |
| | MATING AND UNMATING FORCES | Must be suitable for the std. value. | | - | - | kof | - | - |
| 9 | HUMIDITY | Insulation resistance must be over the std. value at 40±2°C 90-95% 96 hours. at high humidity after high humidity | MIL-STD-1344 | 1000 | - | MΩ | ○ | - |
| 10 | VIBRATION | Must have no damage, crack and looseness of parts at Frequency range 10-55 Hz, amplitude 0.75mm-G at 2 hours for 3 directions. | MIL-STD-1344 | - | - | - | ○ | - |
| 11 | SHOCK | Must have no damage, crack and looseness of parts after 3 cycles at 490m/s in 3 directions. | MIL-STD-1344 | - | - | - | ○ | - |
| 12 | TEMPERATURE CYCLING | Must have no damage, crack and looseness of parts for -55 ~ +85°C 5 cycles. | MIL-STD-1344 | - | - | - | ○ | - |
| 13 | DURABILITY UNIT CONTACT CONTACT | Must be less than the std. value after 30 insertion and extraction cycles at the condition described in above item No.4. | MIL-STD-1344 | - | 30 | mΩ | ○ | - |
| 14 | SALT SPRAY (CORROSION). | Must not have heavy corrosion after salt water spray for hours. | | - | - | - | - | - |
| 15 | H ₂ S-EXPOSURE | Must not have heavy corrosion after ppm for hours. | | - | - | - | - | - |
| 16 | SO ₂ -EXPOSURE | Must not have heavy corrosion after ppm for hours. | | - | - | - | - | - |

Notes:1
This temperature includes a rise by heat's generation of connector when electricity passes.

| | | | | |
|----------------|----------|---------------------|---------|---|
| REMARKS | APPROVED | <i>H. J. ...</i> | 94.3.25 | ISSUED BY HR5 HIROSE ELECTRIC CO., LTD. |
| | REVIEWED | | | |
| | CHECKED | J. Oma | 94.3.25 | |
| | DESIGNED | M. Gotoh | 94.3.24 | |
| | DRAWN | M. Gotoh | 94.3.24 | |
| DRAWING No. | | SPECIFICATION SHEET | | PART No. DF1B-X-DS-2.5RC |
| SLC4-160092-02 | | CODE No. | | 0600 4 CL541-0650-2 |

