

| APPLICABLE STANDARD | | | | |
|---------------------|-----------------------------|--|---------------------------|------------------------------|
| RATING | OPERATING TEMPERATURE RANGE | -35°C TO +85°C(NOTES 1) | STORAGE TEMPERATURE RANGE | -10°C TO +60°C(NOTES 3) |
| | OPERATING HUMIDITY RANGE | 20% TO 80%(NOTES 2) | STORAGE HUMIDITY RANGE | 40% TO 70%(NOTES 2)(NOTES 3) |
| | VOLTAGE | 30V AC | APPLICABLE CONNECTOR | DF56※-40P-0.3SD(##) |
| | CURRENT | AWG#42:0.2A AWG#44:0.15A (NOTES 4) AWG#46:0.1A | | |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|---------------------|---------------------------------------|-----------------------|----|----|
| CONSTRUCTION | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | X | X |

| ELECTRIC CHARACTERISTICS | | | | |
|---------------------------------|-------------------------|--|---|---|
| CONTACT RESISTANCE | 100m A (DC OR 1000 Hz). | CONTACT:80mΩ MAX. SHIELDING:80mΩ MAX. | X | — |
| INSULATION RESISTANCE | 100V DC. | 50MΩ MIN. | X | — |
| VOLTAGE PROOF | 100V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | X | — |


| MECHANICAL CHARACTERISTICS | | | | |
|-----------------------------------|--|---|---|---|
| MECHANICAL OPERATION | 20TIMES INSERTIONS AND EXTRACTIONS. | ① CONTACT RESISTANCE: NO VARIATION OF 50 mΩ OR MORE FROM INITIAL VALUE. SHIELDING RESISTANCE: NO VARIATION OF 50 mΩ OR MORE FROM INITIAL VALUE. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | — |
| VIBRATION | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, 3 DIRECTIONS × 10 CYCLE. | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | — |
| SHOCK | 490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | | X | — |

| ENVIRONMENTAL CHARACTERISTICS | | | | |
|--------------------------------------|---|--|---|---|
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55 → +85 °C TIME 30 → 30 min UNDER 5 CYCLES. (THE TRANSFERRING TIME OF THE CHAMBER IS 2-3 MINUTE.) | ① CONTACT RESISTANCE: NO VARIATION OF 50 mΩ OR MORE FROM INITIAL VALUE. SHIELDING RESISTANCE: NO VARIATION OF 50 mΩ OR MORE FROM INITIAL VALUE. | X | — |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h. | ① CONTACT RESISTANCE: NO VARIATION OF 50 mΩ OR MORE FROM INITIAL VALUE. SHIELDING RESISTANCE: NO VARIATION OF 50 mΩ OR MORE FROM INITIAL VALUE. ② INSULATION RESISTANCE: 25 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | — |
| SULFUR DIOXIDE GAS | EXPOSED IN 10-15 PPM 96h. | NO DEFECT SUCH AS CORROSION WHICH IMPAIRS THE FUNCTION OF CONNECTOR. | X | — |
| RESISTANCE TO SOLDERING HEAT | ① REFLOW TEMPERATURE: PEAK 250°C MAX 240°C MIN :20 sec MAX 220°C MIN :60 sec MAX ② MANUAL SOLDERING TEMPERATURE: 350°C, 3sec MAX. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | X | — |
| SOLDERABILITY | SOLDERED AT SOLDER TEMPERATURE, 245°C FOR INSERTION DURATION, 5 sec. (Sn-3.0Ag-0.5Cu) | SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSSED. | X | — |

| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|-------|--------------------------|----------|---------|------|
| △ | | | | |

| | | | |
|--|----------|--------------|------------|
| REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT NOTE2: NON CONDENSING NOTE3: THE TERM "STORAGE" REFERS TO PRODUCTS STORED FOR A LONG PERIOD PRIOR TO MOUNTING AND USE. THE OPERATING TEMPERATURE AND HUMIDITY RANGE COVERS THE NON-CONDUCTING CONDITION OF CONNECTORS AFTER BOARD MOUNTING AND THE TEMPORARY STORAGE CONDITIONS OF TRANSPORTATION, etc NOTE4: TEMPERATURE RISE OF CONNECTOR BODY ONLY, AND THAT OF CASE IS NOT INCLUDED. Unless otherwise specified, refer to JIS C 5402,IEC60512. | APPROVED | TS. SAKATA | 10. 07. 29 |
| | CHECKED | IO. DENPOUYA | 10. 07. 29 |
| | DESIGNED | AH. MIYAZAKI | 10. 07. 29 |
| | DRAWN | AH. MIYAZAKI | 10. 07. 29 |

| | | |
|--|-------------|----------------|
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | DRAWING NO. | ELC4-324300-01 |
|--|-------------|----------------|

| | | | |
|---|---------------------------|----------|---------------------|
|  | SPECIFICATION SHEET | PART NO. | DF56-40S-0. 3V (51) |
| | HIROSE ELECTRIC CO., LTD. | CODE NO. | CL662-5600-0-51 |