

# Flat Cable EMI Suppression Cores (2643166551)



Part Number: 2643166551

43 FULL FLAT CABLE CORE

Explanation of Part Numbers:

- Digits 1 & 2 = Product Class
- Digits 3 & 4 = Material Grade

**Flat cable suppression core can accommodate multi- conductors flat cables, in widths from 12.7 mm (0.500") up to 77 mm (3.0"). These flat cable cores are available in two ferrite material grades to reduce conducted EMI from 1 MHz to hundreds of MHz.**

Our Expanded Cable & Suppressor Kit (part number 0199000005) contains a selection of these flat cable cores and clips.

Flat Cable Cores are available in selected sizes in the Flex Circuit & Ribbon Cable Core Kit (part number 0199000038).

Assembly clips are available for most of the split flat cable cores. See section Flat Cable Cores Assembly clips.

Weight: 71 (g)

Dim	mm	mm tol	nominal inch	inch misc.	Cable Information			
A	45.1	±0.75	1.775	-	Max Diameter	Max Dimension	Solid Equivalent	Flat Cable Cores
B	34.4	±0.70	1.355	-	0	33.70 x 1.20	-	-
C	28.6	±0.70	1.125	-				
D	12.45	±0.40	0.49	-				
E	1.5	±0.30	0.06	-				

**Chart Legend**  
+ Test frequency

•For assembly clips see Flat Cable Cores Assembly Clips

Typical Impedance (Ω)	
10 MHz	67
25 MHz <sup>+</sup>	115
100 MHz <sup>+</sup>	300
250 MHz	415

Flat cable suppression cores, split or single cores, are controlled for impedances only. Minimum impedance values are specified for the + marked frequencies. The minimum impedance is typically the listed impedance less 20%.

Centered, single turn impedance tests for the 31 and 43 material parts are performed on the 4193A Vector Impedance Analyzer. All tests are made with the shortest practical wire length.

