




CUSTOMER PRINT

PART NUMBER: W8C8X-6PG-5XX_CD

NOTES:
 1. ALL PARTS TO BE BULK PACKED.
 2. SEE DRAWING HPMIMIX FOR HOLE PATTERN.
 3. DIMENSIONS ARE FOR REFERENCE ONLY.

CONNECTOR P/N	POSITIONS		CONTACT STYLE	CABLE O.D. RANGE
	#16	#20		
W8C80-6PG-513	2	4	CRIMP	0.13-0.15" (3.3 -3.8 mm)
W8C80-6PG-516			CRIMP	0.16-0.18" (4.1 -4.6 mm)
W8C80-6PG-519			CRIMP	0.19-0.21" (4.8 -5.3 mm)
W8C80-6PG-522			CRIMP	0.22-0.25" (5.6 -6.3 mm)
W8C80-6PG-528			CRIMP	0.26-0.285" (6.6 -7.2 mm)
W8C82-6PG-513			SOLDER	0.13-0.15" (3.3 -3.8 mm)
W8C82-6PG-516			SOLDER	0.16-0.18" (4.1 -4.6 mm)
W8C82-6PG-519			SOLDER	0.19-0.21" (4.8 -5.3 mm)
W8C82-6PG-522			SOLDER	0.22-0.25" (5.6 -6.3 mm)
W8C82-6PG-528			SOLDER	0.26-0.285" (6.6 -7.2 mm)



CUSTOMER APPROVAL

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION.

APPROVED BY: _____
 DATE: _____

PRELIMINARY

RoHS COMPLIANT

0A	PNK	01-19-16	PDR 14001 PRELIMINARY
REV.	INIT.	DATE	DESCRIPTION
	PNK	01-19-16	ORIG. DRAWN BY: DATE: 01-19-16
			CHECKED BY:
			APPROVED BY:
	SCALE	SIZE	SHEET
	NTS	B	1 OF 1
	FILE:	DIRECTORY:	PART NUMBER:
	W8C8X-6PG-5XX_CD	SLW	W8C8X-6PG-5XX_CD
			REV 0A

ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF CONXALL CORPORATION. UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.

ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS. UNLESS OTHERWISE SPECIFIED TOLERANCES: 3 PLACE DECIMALS ±.005 ANGLES ±1° FRACTIONS ±1/16

△ - CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX

conxall
 601 E. WILDWOOD VILLA PARK, IL 60181

TITLE: CABLE-TO-CABLE CONNECTOR
 2-16 + 4-20 PIN CONTACTS
 MINI-CON-X POWER/SIGNAL
 CUSTOMER: STANDARD PRODUCT