

Specification Sheet

Part Number: 596-00326

HellermannTyton Solar Label, BIPOLAR SOLAR ARRAY, 3.75" x 2.0", VL, Red, 50/pkg

Article Number	596-00326
Type	BIPOLARPV
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">• Made with UV stable inks and materials for durability and weather resistance.• The labels are supplied with aggressive adhesive to ensure long life.• Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	reel

Product Description

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, BIPOLAR SOLAR ARRAY, 3.75" x 2.0", VL, Red, 50/pkg
Global Part Name	BIPOLARPV-V-RD
Technical Description	Pre-Printed Solar Label, 3.75" X 2", BIPOLAR SOLAR ARRAY, Red
Width W (Imperial)	3.75
Width W (Metric)	92.25
Height H (Imperial)	2.0
Height H (Metric)	50.80
Material	Vinyl
Material Shortcut	V
Adhesive	Acrylic
Halogen free	Yes
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
ROHS Complaint	Yes
Certification/Specification WEB	NEC2011 UL 969 IFC 2012

Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919905060
Labels per Column	1
Labels per Row	1
Weight (Metric)	.104
Weight (Imperial)	0.23