

## Specification Sheet

Part Number: MMB.50C2



Masonry Cable Tie Mount, 1.24" Long, .25" Hole Dia, .18" Max Cable Tie Width, PA46, Black, 100/pkg

<b>Article Number</b>	151-00116
<b>Type</b>	MMB.5
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Masonry Mounts provide a permanent solution when fastening wire and cables to masonry surfaces.</li><li>•The mounts have easy installation into predrilled holes allowing for faster use.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton Masonry Mounts provide a permanent method of attaching wire and cable to masonry surfaces. Masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications.
<b>Short Description</b>	Masonry Cable Tie Mount, 1.24" Long, .25" Hole Dia, .18" Max Cable Tie Width, PA46, Black, 100/pkg

**Global Part Name**

MMB.5-PA46-BK

**Length L (Imperial)**

1.24

**Length L (Metric)**

31.5

**Fixation Method**

with Fir Tree (Mounts)

**Width W (Imperial)**

0.375

**Width W (Metric)**

9.5

**Cable Ties**

T18 - T50

**Height H (Imperial)**

.37

**Height H (Metric)**

9.40

**Cable Tie Width Max (Imperial)**

0.18

**Cable Tie Width Max (Metric)**

4.6

**Mounting Hole Diameter D (Imperial)**

0.25

**Mounting Hole Diameter D (Metric)**

6.35 mm

**Mounting Hole Diameter D Max (Metric)**

6.35

**Material**

Polyamide 4.6 (PA46)

**Material Shortcut** PA46

**Flammability** UL 94 V2

**Operating Temperature (Metric)** -40°F to +266°F (-40°C to +130°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909987

**Content Unit(BMEcat)** pcs.