

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case that the application demands a high level of reliability, such as automotive,  
 please contact a company representative for further information.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-10°C ~ 60°C	STORAGE TEMPERATURE RANGE	-10°C ~ 60°C	
	POWER	-	CHARACTERISTIC IMPEDANCE	-	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK			APPROVED	HO. MIWA	06. 12. 11
			CHECKED	SJ. SHIMIZU	06. 12. 11
			DESIGNED	TS. ITO	06. 12. 08
			DRAWN	TS. ITO	06. 12. 08
Unless otherwise specified, refer to JIS C 5402.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-025739-01	
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	TM-4-DC1	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL222-1364-6-00	1/1