

APPLICABLE STANDARD				
RATING	Operating temperature range	-25 °C TO +85 °C	Storage temperature Range	-10 °C TO +60 °C
	Voltage	_____	_____	_____
	Current	2 A	Applicable cable	AWG#18 TO 22 (Jacket diameter ϕ 1.7 Max.)

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

General examination	Visually and by measuring instrument.	According to drawing.	X	X
Marking	Confirmed visually.		X	X

ELECTRIC CHARACTERISTICS

Contact resistance	Contact shall be measured AT DC 1 A	15 m Ω MAX.	X	-
--------------------	-------------------------------------	--------------------	---	---

MECHANICAL CHARACTERISTICS

Contact insertion and withdrawal forces	ϕ 0.57 ⁰ _{-0.003} By steel gauge.	Insertion and withdrawal forces : 0.15 N MIN.	X	-
Mechanical operation	1000 times insertions and extractions.	Contact resistance: 20 m Ω MAX.	X	-
Tensile strength (crimped connection)	Crimped only connector of the applicable wire and pulling the applicable wire	AWG #22 (16/ ϕ 0.16) : 54 N MIN. AWG #20 (27/ ϕ 0.16) : 60 N MIN. AWG #18 (42/ ϕ 0.16) : 90 N MIN.	X	-

ENVIRONMENTAL CHARACTERISTICS

Corrosion salt mist	Exposed in 5 % salt water spray for 48 h.	No heavy corrosion ruin the function.	X	-
---------------------	---	---------------------------------------	---	---

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0				

REMARK Unless otherwise specified, refer to IEC 60512 (JIS C 5402).	APPROVED	EJ.KUNII	16.02.25
	CHECKED	EJ.KUNII	16.02.25
	DESIGNED	MM.ISHII	16.02.24
	DRAWN	MM.ISHII	16.02.24

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC-010243-00-00
--	-------------	------------------

HRS	SPECIFICATION SHEET	PART NO.	RP17-SC-212	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL113-0509-2-00	1/1

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive,
 please contact a company representative for further information.