



TG100™

September 2009

PRODUCT DESCRIPTION

TG100™ provides the following product characteristics:

Technology	Silicone grease
Appearance	Grey
Application	Thermal management
Typical Assembly Applications	CPUs, GPUs, MCUs, ASICs, DC-DC converters, IGBT and Transistors
Operating Temperature	-40 to 150 °C

TG100™ is recommended for high-temperature heat transfer in normal applications. It is used between heat generating devices and the surfaces to which they are mounted or other heat dissipating surfaces. This product delivers excellent thermal resistance, offers high thermal conductivity and virtually no evaporation over a wide operating temperature range. It is nonflammable, oxidation resistant and does not promote rust or corrosion.

TYPICAL PROPERTIES

Viscosity, Cone & Plate, mPa·s (cP):	
Temperature: 25 °C, Shear Rate: 0.5 s ⁻¹	350,000
Specific Gravity @ 25 °C	1.94
Thermal Conductivity, W/mk	3.4
Thermal Impedance ASTM-D-5470, °C.in ² /W: 80psi	0.017

GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

DIRECTIONS FOR USE

1. For best results parts to be covered should be clean and free of oil and debris.
2. Apply appropriate material to substrate so that there is enough material to cover 100% of the surface between the component and the heat sink and the material leaves a small fillet.
3. Place the heat sink on top of the component and secure with clips, screws or other hardware.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 5°C to 30°C. Storage below 5°C or greater than 30°C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

Conversions

(°C x 1.8) + 32 = °F
kV/mm x 25.4 = V/mil
mm / 25.4 = inches
N x 0.225 = lb
N/mm x 5.71 = lb/in
N/mm ² x 145 = psi
MPa x 145 = psi
N·m x 8.851 = lb·in
N·m x 0.738 = lb·ft
N·mm x 0.142 = oz·in
mPa·s = cP

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0



Americas
+1.949.789.2500

Europe
+44.1442.278.000

Asia
+86.21.2891.8000

For the most direct access to local sales and technical support visit: www.henkel.com/electronics