

Device connector, front mounting - RC-07P1N12WB00 - 1594419

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Device connector for front wall, straight, shielded: yes, Screw locking, M23, Number of positions: 7, Type of contact: Male connector, Solder connection, Axial O-ring, 4x Ø3.2

The figure shows the 12-pos. product version



Key Commercial Data

Packing unit	1 STK
Custom tariff number	85366990
Country of origin	Germany


Technical data

Product type	Circular connectors (device side)
Approval	EAC
Number of positions	7
Coding	N
Type	Device connector for front wall
Mounting type	4x Ø3.2
Rated current (IEC)	20
Rated voltage (IEC)	300
Thread	M23
Shielding	yes
Signal type	Signal

Drawings

Device connector, front mounting - RC-07P1N12WB00 - 1594419

Schematic diagram



Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440103
eCl@ss 9.0	27440102

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC001121

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

EAC

Ex Approvals

Device connector, front mounting - RC-07P1N12WB00 - 1594419

Approvals

Approval details

EAC B.01742
