

A	REVISIONS	BY	CHKD	DATE	A	REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD				
RATING	VOLTAGE	CONTACT NO. 1 ~ *	AC 150 V DC V	APPLICABLE CABLES
	CURRENT	CONTACT NO. 1 ~ *	A	IMPEDANCE FREQUENCY RANGE
	POWER			OPERATING TEMPERATURE RANGE
	SPECIALTY			

## SPECIFICATIONS

No.	ITEM	CONDITIONS	TEST STANDARD	MIN	MAX	UNITS	QT.	AT
1	DESIGN-MATERIAL-FINISH	<del>AC</del> Applicable Std. and Ebc 3-083675-01		-	-	-	○	○
2	MARKING			-	-	-	○	○
3	INSULATION RESISTANCE	Must be over standard value at DC V.	MIL-STD-1344	500	-	MΩ	○	-
4	CONTACT RESISTANCE	The voltage drop must be under the Std. value at DC A.		-	-	mΩ	-	-
	CONTACT	The voltage drop must be under the Std. value at DC A.		-	-	mΩ	-	-
5	DIELECTRIC WITHSTANDING VOLTAGE	Must withstand AC 500V for one minute. DC	MIL-STD-1344	-	-	-	○	-
6	LOW LEVEL CIRCUIT	The Contact Resistance must be under the Std. value at DC 20mV less and mA.		-	-	mΩ	-	-
7	DRY CIRCUIT	Must have conductivity in alternate current at DC μV.		-	-	-	-	-
8	CONTACT ENGAGEMENT AND SEPARATION FORCES	Must be suitable for the Std. gauge size value at applicable gauge.		-	-	N	-	-
	MATING AND UNMATING FORCES	Must be suitable for the Std. value.		-	-	N	-	-
9	HUMIDITY	Insulation resistance must be over the Std. value at 40±2% 90-95% 96 hours. at high humidity after high humidity	MIL-STD-1344	500	-	MΩ	○	-
10	VIBRATION	Must have no damage, crack and looseness of parts at Frequency range 10-55 Hz, Total amplitude 1.5 mm, at 2 hours for 3 directions.	MIL-STD-1344	-	-	-	○	-
11	SHOCK	Must have no damage, crack and looseness of parts after 3 cycles at 490 m/s <sup>2</sup> in 3 directions.	MIL-STD-1344	-	-	-	○	-
12	TEMPERATURE CYCLING	Must have no damage, crack and looseness of parts for -55 ~ +85°C 3 cycles. Total 5 hours.	MIL-STD-1344	-	-	-	○	-
13	DURABILITY	Must be less than the Std. value after insertion and extraction cycles at the condition described in above item No. 4.		-	-	mΩ	-	-
	CONTACT					mΩ	-	-
14	SALT SPRAY (CORROSION).	Must not have heavy corrosion after salt water spray for hours. X		-	-	-	-	-
15	H <sub>2</sub> S-EXPOSURE	Must not have heavy corrosion after ppm for hours.		-	-	-	-	-
16	SO <sub>2</sub> -EXPOSURE	Must not have heavy corrosion after ppm for hours.		-	-	-	-	-

Notes: 1  
This temperature includes a rise by heat's generation of connector when electricity passes.

REMARKS X = Number of contacts	APPROVED	<i>[Signature]</i>	'94.4.25	ISSUED BY  <b>HR5 HIROSE ELECTRIC CO., LTD.</b>	
	REVIEWED				
	CHECKED	<i>K. Akiyama</i>	'94.4.25		
	DESIGNED	<i>S. Taniwaki</i>	'94.4.19		
	DRAWN	<i>T. Joo</i>	'94.4.16		
DRAWING No. ELC4-083675-01				PART No. DF13-XS-1.25C	
SPECIFICATION SHEET				CODE No. CL536-0001 4 0014-6-	

Apr. 1. 2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

TO

