

Fuseholder Open Design, Holder for MSF 125, horizontal, THT



125 VAC · 5 A (UL/CSA)

See below:

[Approvals and Compliances](#)

### Description

- Through hole mounting
- Horizontal mount

### References

Fuseholder to [MSF 125](#); [MSU 125](#)

### Weblinks

[pdf datasheet](#), [html-datasheet](#), [General Product Information](#), [Packaging details](#), [Distributor-Stock-Check](#), [Detailed request for product](#), [Microsite](#)

### Technical Data

Fuse-Link	Microfuse 125 V	Soldering Methods	Wave
Mounting	PCB		<a href="#">Soldering Profile</a>
Terminal	Solder THT	Solderability	245 °C / 3 sec acc. to IEC 60068-2-20, Test Ta, method 1
Rated Voltage	125 VAC	Resistance to Soldering Heat	260 °C / 5 sec acc. to IEC 60068-2-20, Test Tb, method 1A
Rated current	5 A (UL/CSA)	Contact Resistance	< 10 mΩ at 20 mV
Admissible Ambient Air Temp.	-40 °C to 85 °C	Dielectric Strength	> 2.5 kV between life parts (50 Hz; 1 min)
Climatic Category	40/085/21 acc. to IEC 60068-1	Impulse Withstand Voltage	> 4 kV between life parts
Material: Socket	Thermoplastic, black, UL 94V-0	Insulation Resistance	> 10 MΩ between life parts (500 VDC; 1 min)
Material: Terminals	Silver-Plated Copper Alloy		
Unit Weight	0.34 g		
Storage Conditions	0 °C to 60 °C, max. 70% r.h.		
Product Marking			

### Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

### Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: FMR

Approval Logo	Certificates	Certification Body	Description
	<a href="#">UL Approvals</a>	UL	UL File Number: E39328

### Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	UL 4248-1	Fuseholder general requirements
	Designed according to	CSA C22.2 no. 4248.1	Fuseholder general requirements





### Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
	Designed for applications acc.	IEC/UL 60950	IEC 60950-1 includes the basic requirements for the safety of information technology equipment.

**Compliances**

The product complies with following Guide Lines

Identification	Details	Initiator	Description
	<a href="#">CE declaration of conformity</a>	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	RoHS	SCHURTER AG	EU Directive RoHS 2011/65/EU
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

**Dimension [mm]**



Drilling diagram

**All Variants**

Holder	Order Number
●	0031.7505

Most Popular.

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

**Packaging Unit**

Plastic Bag (100 pcs.)