



P.C.B LAYOUT

NOTES:  
 MATERIAL:  
 CONTACTS:BRASS T=0.25mm  
 INSULATOR:PTI+30%G.F. UL 94V-0  
 FRONT SHELL:BRASS T=0.30mm  
 BACK SHELL:SPCC T=0.30mm  
 SPRING:SPCC  
 MECHANICAL:  
 MATING:35N MA  
 WITHDRAWAL FORCE:10N MIN  
 DURABILITY:1500CYCLES MIN  
 ELECTRICAL:  
 CURRENT RATING:1.5A  
 VOLTAGE RATING:30V  
 WITHSTANDING VOLTAGE:750V AC  
 CONTACT RESISTANCE:25mΩ MAX  
 INSULATION RESISTANCE:1000MΩ MIN  
 PLATING  
 CONTACTS:GOLD FLASH AND TIN OVER NICKEL PLATED  
 SHELL:NICKEL OVER ALL PLATING  
 ENVIRONMENTAL:  
 TEMPERATURE RANGE:-55°C TO+85°C

10/01/30	ING	EG-N1012072			A3
09/12/29	BENDEE	EG-H12067	變更尺寸標注位置		A2
DATE	DR.BY	EEN.NO.	DESCRIPTION	MARK	VER.

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差參考表									
X.X	±0.38					X.X°	±2.0°		
X.XX	±0.25	X.XX°	±1.0°	CHECK:	DATE	SCALE	UNIT	TYPE	PAGE
X.XXX	±0.13	X.XXX°	±0.5°	DRAW:	2010.01.30	1:1	mm	CD	1/1

TITLE: USB 8P A/F 雙層DIP 90 雙彈片30U"成品		PRODUCT NO: 1002-004-01010			
---	--	----------------------------	--	--	--