

## Specification Sheet

Part Number: 181-00026



Slotted Wall Wiring Duct, 3" X 2", Adhesive, PVC, Black, 120ft/Carton

**Article Number**

181-00026

**Type**

SLA3X2

**Color**

Black (BK)

**Features & Benefits**

- Strong fingers prevent unwanted breaking.
- Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.
- Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.

**Quantity Per**

carton

**Product Description**

Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".

**Short Description**

Slotted Wall Wiring Duct, 3" X 2", Adhesive, PVC, Black, 120ft/Carton

**Global Part Name**

SLA3X2-PVC-BK

**Technical Description**

Adhesive

**Length L (Imperial)**

6.0

**Length L (Metric)**

1.83

**Width W (Imperial)**

3.0

**Width W (Metric)**

76.2

**Height H (Imperial)**

2.07

**Height H (Metric)**

52.60

**Mounting Hole Centers (Imperial)**

4.0

**Material**

Polyvinylchloride (PVC)

**Material Shortcut**

PVC

**Flammability**

Self-Extinguishing

**Halogen free**

No

**Operating Temperature (Metric)**

+122°F (+50°C)

**Reach Complaint(Article 33)**

No

<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL CSA EN 50085-2-3_1A EN 50085-1:2005 + A1:2013
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	120
<b>Package Quantity (Metric)</b>	36.58
<b>Customs Number</b>	3925900000