

## 76302WS Multi-Conductor - 300V Foil/Spiral Shield, Continuous Flexing Data Applications Up to 6 Million Flex Life Cycles



For more Information  
please call

1-800-Belden1

### General Description:

22 AWG stranded (19x34) tinned copper conductors, PVC insulation, Aluminum/Polyester Foil Shield, Tinned copper spiral shield, 90% coverage, oil-resistant PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
2	22	19x34	TC - Tinned Copper

#### Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.010

Insulation Color Code Chart:

Number	Color
1	Black
2	Red

#### Outer Shield

Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Tape	Aluminum/Mylar	100.000
2	Serve	TC - Tinned Copper	90.000

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.040

#### Overall Cable

Overall Nominal Diameter: 0.208 in.

### Mechanical Characteristics (Overall)

Bulk Cable Weight: 30 lbs/1000 ft.

Max. Recommended Pulling Tension: 16.700 lbs.

Min. Bend Radius/Minor Axis: 1.700 in.

Min. Bend/Installation: 1.700 in.

Min. Bend Radius (Continuous Flexing): 1.700 in.

Flex Cycle Rating: 6 Million Flexes

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

MIL Order #39 (China RoHS): Yes

Customer Part Number Reference Specification: AWM/STYLE 10002, AWM/STYLE 2661, CSA AWM I/II A/B, EU Directive 2011/65/EU(RoHS2), REACH Regulation (EC 1907/2006), California Proposition 65

#### Flame Test

CSA Flame Test: FT4

#### Suitability

Suitability - Burial: Yes

### Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Description	Impedance (Ohm)
Characteristic Impedance	45.000

## ENGLISH MEASUREMENT VERSION

### 76302WS Multi-Conductor - 300V Foil/Spiral Shield, Continuous Flexing Data Applications Up to 6 Million Flex Life Cycles

**Nom. Inductance:**

**Inductance (µH/ft)**

0.170

**Nom. Capacitance Conductor to Conductor:**

**Freq. (MHz)    Capacitance (pF/ft)**

0.001            43.000

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**

15.300

**Nominal Outer Shield DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**

5.800

**Max. Operating Voltage - UL:**

**Voltage**

300V

#### Notes (Overall)

**Notes:** Temperature Range -10 to 105°C(static), +5 to 105°C (dynamic)

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0    Revision Date: 09-27-2017

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.