

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive,
 please contact a company representative for further information.

APPLICABLE STANDARD				
RATING	Operating temperature range.	-25°C to +85°C	Storage temperature range.	-10°C to +60°C
	_____	_____	_____	_____
	_____	_____	_____	_____

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

General examination.	Visually and by measuring instrument.	According to drawing.	X	X
Marking	Confirmed visually		X	X

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0				

REMARK	APPROVED	EJ.KUNII	15.08.27
	CHECKED	EJ.KUNII	15.08.27
	DESIGNED	TP.KOMATSU	15.08.27
	DRAWN	TP.KOMATSU	15.08.27

Unless otherwise specified, refer to IEC 60512.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC-021623-01-01
--	-------------	------------------

HRS	SPECIFICATION SHEET	PART NO.	HR10-7R-C(01)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL110-0058-6-01	1/1