



Wire \_\_\_\_\_ Tinned copper  
 Gauge \_\_\_\_\_ AWG 28/7 0,089 mm<sup>2</sup>  
 Voltage rating \_\_\_\_\_ 300 Vr.m.s  
 Current rating \_\_\_\_\_ 2,1A at 25°C  
 Capacity unbalanced \_\_\_\_\_ 45,9 pF/m at 1 MHz  
 Impedance unbalanced \_\_\_\_\_ 105 Ω  
 Propagation delay \_\_\_\_\_ 4,9 ns/m nominal  
 Insulation material \_\_\_\_\_ PVC  
 Temperature rating \_\_\_\_\_ -20°C (operating) to +105°C  
 \_\_\_\_\_ -30°C (static)  
 Flammability rating \_\_\_\_\_ Flame retardant VW1  
 Insulation resistance \_\_\_\_\_ 100 MΩ/km  
 Approval \_\_\_\_\_ UL AWM style 2651

										Dat. Name Detail. 20/10/05 JMDR Insp. _____ Stand. _____		All Dim. in mm Orig. Size DIN A 4		SEK 18 flat cable 34 poles		Maßstab/ Scale 10:1	
09 18 034 7004		100 m (328 feet)		EC01360		19/02/10		SC		HARTING EURL F-95972 Paris		TB 09 18 034 700X		Blatt/ Page 1 / 1			
09 18 034 7001		30,48 m (100 feet)		34400		17/09/07		PK		HARTING							
Part number		Length per reel		Mod.		Dat.		Name				Sub.					